

Baifa Generating Set Model	BF-D106	
	Prime	Standby
Gen-Set Power (KW/KVA)	72/90	80/100
Engine Power (KW)	90	
Engine Model	TD226B-6D	
Engine Manufacturer	Sino-Germany joint venture Weichai-Deutz Co., Ltd	
Engine Configuration	6-cylinder in line, 4-stroke, exhaust gas turbocharged, direct spray fuel system	
Engine Cooling Mode	The Radiator suitable for 40°C Temperature, Strap drive the cooling fan with protection cover	
Speed Control System	Mechanical speed controller, electricity-magnet valve control switch	
Start Mode	24V Direct Current Start, Including alternator & battery	
Engine Filter System	Dry air filter type, Fuel filters, Lube filter	
Engine total displacement (L)	6.23	
Compress ratio	16.0:1	
Bore * Stroke (mm)	105 * 120	
100%Load fuel consumption (L/h)	20.8	22.7
Specific fuel consumption (g/kwh)	≤205	
Lubricating oil consumption (g/kwh)	≤1.36	
Exhaust Air Flow (m ³ /min)	90	
Air consumption (m ³ /min)	6	
Exhaust gas Flow (m ³ /min)	14.5	
Exhaust gas Temperature (°C)	480	
Oil Capacity (L)	13	
Coolant Capacity (L)	25.8	
Generator model	Single bearing alternator	
Short circuit Protection	MCCB Air Switch	

Rated Voltage /Frequency /Power Factors	400V/230V, 50Hz, 0.8 lag, 3-phase & 4-line
Stable Frequency Change Rate	≤5%
Free Load Voltage Adjusting Range	≥95%-105%
Stable Voltage Regulator	≤±1%
Insulation Class/ Protection Grade	H Class/IP23
Telephone Influence Factor	TIF < 50/ THF < 2%
Accessory Attached	A suit of start battery& connective wire; Exhaust smoke siphon, Ripple absorber, Flange, Muffler; Absorber on base
Water tank ventilation area (mm)	700 * 820
Dimension of open type (mm)	2350 * 850 * 1900
Weight with fuel tank on base (kg)	1150
Dimension of soundproof type (mm)	3230 * 1170 * 1800
Weight with fuel tank on base (kg)	1790



PHOTO FOR REFERENCE ONLY